

TECHNICAL DATA SHEET FOR E32D5 ON THE P12M Proofer/Holding Cabinet

Full Size Digital / Electric Convection Oven on a
12 Tray Manual / Electric Proofer/Holding Cabinet

STANDARD FEATURES

- Full size sheet pan capacity
- 5 tray Oven / 12 tray Proofer
- Compact 28⁷/₈" / 735mm width
- Low unit height 69⁷/₈" / 1775mm
- Side hinged doors (standard LH hinge)
Optional RH hinge (field convertible)
- Dual halogen lamps in Oven and Proofer
- Proofer with dual function Proof and Holding modes

OVEN

- 3¹/₈" / 85mm tray spacing
- Electronic digital display Time and Temperature controls
- Programmable for up to 20 programs
- Water injection mode
- High performance bi-directional reversing fan system
- Safe-Touch vented door
- Porcelain enameled oven chamber
- Plug-in continuous oven door seal
- 5 oven wire racks supplied
- 100% recyclable packaging

PROOFER

- 2⁷/₈" / 74mm tray spacing
- Auto water fill system with optional integrated water filter kit
- Continuous door seal
- Low velocity circulation fan system
- Mechanical thermostat and Humidity level control
- Cabinet temperature display thermometer
- 4 dia. 3" / 76mm castors with 2 front castors dual wheel and swivel lock, 2 rigid rear castors
- 100% recyclable packaging

ACCESSORIES

- Optional 3M Cuno water filter kit complete with cartridge and connection fittings
- Installs in pre-fitted rear housing of cabinet for flush rear installation



E32D5 Unit shall be a Moffat electrically heated Turbofan convection oven E.T.L. listed and NSF-4 listed. The oven shall have a one piece porcelain enameled oven chamber, stainless top and sides and safe touch vented easy clean side hinged door that offers field reversible hinging. Oven shall have capacity for five full size sheet pans. The oven shall be controlled by an electronic control having separate digital displays and adjusting knobs for time and temperature functions. The oven control shall allow both manual and programmed operating modes and have separate control keys for water injection, oven light function and timer operation. The unit shall include dual halogen oven lamps. Unit shall be supplied in 100% recyclable shipping packaging.

P12M Unit shall be a Moffat electrically heated Turbofan Proofer and Holding Cabinet ETL Listed and NSF-4 listed. The proofer and holding cabinet shall have double skin construction with stainless steel interior and exterior sides, front and top. Door shall be side hinged and field reversible. Unit shall have capacity for up to 24 half size sheet pans or 12 full size sheet pans. A single speed fan shall gently and evenly circulate air around the cabinet. Cabinet shall be controlled by a mechanical thermostat and humidity via a control of the water tank. A thermometer shall indicate the cabinet temperature. Proofer and holding cabinet shall be mounted on castors, with two rigid castors at rear and two swivel castors dual swivel and wheel lock and front. Proofer and Holding Cabinets shall be fitted with NEMA 5-20P cordsets. Unit shall be supplied in 100% recyclable shipping packaging.



www.moffat.com

U.S.A.
 Moffat Inc
 3765 Champion Boulevard
 Winston-Salem
 North Carolina 27105
 Ph Toll Free 1-800-551 8795
 Ph 336-661 0257
 Fax 336-661 9546
 Email sales@moffat.com
 www.moffat.com

E32D5 Full Size Digital / Electric Convection Oven P12M Full Size Manual / Electric Proofer/Holding Cabinet

CONSTRUCTION - Oven (E32D5)

Porcelain enameled fully welded oven chamber
 Stainless steel front, sides and top exterior
 Stainless steel frame side hinged door
 0.2" / 5mm thick door inner and outer glass
 Stainless steel control panel
 Aluminized coated steel base and rear panels

CONSTRUCTION - Proofer (P12M)

304 stainless steel interior cabinet
 Stainless steel front, sides and top exterior
 Stainless steel interior side racks
 Stainless steel frame side hinged door
 0.2" / 5mm thick door glass
 Stainless steel control panel
 Aluminized coated steel base and rear panels

CONTROLS - Oven (E32D5)

Electronic controls with Digital Time and Temperature display,
 Manual or Program modes
 Large ¾" / 20mm high LED displays
 Two individual time and temperature setting control knobs
 ON/OFF key.
 Oven Lamp key (toggle or auto-time off mode settings)
 Timer Start/Stop key
 Water Injection key (manual shot or timed shot mode settings)
 Programs select key
 Actual temperature display key
 Adjustable buzzer/alarm volume
 Thermostat range 150-500°F / 50-260°C
 Timer range from 180 minute in countdown mode /
 999 minute in count-up mode
 Over-temperature safety cut-out

CONTROLS - Proofer (P12M)

Off / Proof / Holding mode selector switch
 Mechanical thermostat 32-185°F / 20-85°C
 Humidity level control
 Cabinet temperature thermometer
 Auto-fill water system standard

CLEANING

Stainless steel top and side exterior panels
 Porcelain enameled oven chamber
 Fully removable stainless steel oven and proofer side racks
 Removable stainless steel oven fan baffle
 Easy clean door system with hinge out door inner glass
 (no tools required)
 Removable plug-in oven door seal (no tools required)

SPECIFICATIONS

Electrical Requirements

Oven (E32D5)
 208V, 60Hz, 1-phase, 5.8kW, 28A
 220-240V, 50/60Hz, 1-phase, 6.5W, 27A
 No cordset supplied

Proofer (P12M)

110-120V, 50/60Hz, 1-phase, 1.95kW, 15.6A
 NEMA 5-20P cordset fitted

Water Requirements

Cold water connection ¾" GHT male
 80psi maximum inlet pressure / 20psi minimum inlet pressure
 Connection to oven optional

External Dimensions

Width 28 7/8" / 735mm
 Height 69" / 1775mm
 Depth 31 1/8" / 810mm

Nett Weight

Oven (E32D5)
 196lbs / 89kg

Proofer (P12M)


194lbs / 88kg

Packing Data

Oven (E32D5)
 231lbs / 105kg
 20.1ft³ / 0.57m³
 Width 29 7/8" / 760mm
 Height 32" / 665mm
 Depth 36 3/8" / 925mm

Proofer (P12M)

236lbs / 107kg
 32.1 ft³ / 0.91m³
 Width 30" / 760mm
 Height 51" / 1295mm
 Depth 36 3/8" / 925mm



Manufactured by:
 Moffat Limited
 16 Osborne Street PO Box 10-001
 Christchurch 8081 New Zealand



ISO9001
 Quality
 Management
 Standard

Designed and manufactured by



ISO9001

All Turbofan products are designed and manufactured by Moffat using the internationally recognised ISO9001 quality management system, covering design, manufacture and final inspection, ensuring consistent high quality at all times.

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd
 Moffat 6.10

